

AUTOMATIC SHRINK SLEEVE LABELING MACHINES

SL1 Series

The **SL1 Series** shrink sleeve labeling machines are designed for use on both tamper evident banding and full body sleeve labeling projects. Their compact design, simple setup instructions, and high speed output allows these machines to excel for use with any in-line bottling or packaging line. There are a number of available options for the **SL1 Series** Sleeveers including Heat Tunnel systems, conveyor lines, and high speed delivery upgrades. The **SL1 Series** machines can achieve a speeds of 150 CPM*. The **SL1 Series** can accommodate film sizes ranging from 16mm - 150mm Lay Flat to a 16mm - 200mm Lay Flat Cut Length.

Key Features

- Up to 150 Containers Per Minute*
- Easy-to-Use Touch Screen Display
- Sanitary Stainless Steel Control Parts
- Simple Setup and Memory Features
- Electric Operation
- Stainless Steel Construction
- Tamper Evident Banding

Optional Features

- Heat Tunnel Additions
- Registration control
- Film Management Sensors
- Conveyor
- High Speed Delivery Upgrade
- Motorized film take-off
- Feed Screw
- Puck Conveyor System



SL2 Series

The **SL2 Series** is designed for speed, accuracy and efficiency at an economic price. Because of their high speed output the **SL2 Series** Sleeveers are an excellent complement to any High Speed In-line or Rotary Bottling line. Utilizing the same design as all our applicators in the **SL series**, and eliminating or reducing the electronics, places the **SL2 Series** Applicators on the cutting edge of sleeve delivery systems. The **SL2 Series** machines can achieve speeds of 300 CPM*. The **SL2 Series** can accommodate film sizes ranging from 16mm - 500mm Lay Flat to a 16mm - 400mm Lay Flat Cut Length. Their compact design can easily accommodate limited production line space.

Key Features

- Up to 300 Containers Per Minute*
- Easy-to-Use Touch Screen Display
- Sanitary Stainless Steel Control Parts
- Simple Setup and Memory Features
- Electric Operation
- Stainless Steel Construction
- Tamper Evident Banding

Optional Features

- Heat Tunnel Additions
- Registration control
- Film management sensors
- Conveyor Lines
- High Speed Delivery Upgrade*
- Motorized film take-off*
- Dual Film Feed
- Puck Conveyor System



SL Series Sleeveers

ACCUTEK
Packaging Equipment Company, Inc.

AUTOMATIC SHRINK SLEEVE LABELING MACHINES



SL1-120 Tamper Evident Bander		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 82" (2082.8 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 120mm	Labeling Speed 100 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3/8" Diameter Max: 3" Diameter



SL2-200		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 200mm	Labeling Speed 300 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3/8" Diameter Max: 5" Diameter



SL1-100		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 82" (2082.8 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 100mm	Labeling Speed 120 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3/8" Diameter Max: 3" Diameter



SL2-300		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 300mm	Labeling Speed 300 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3 3/4" Diameter Max: 7 1/4" Diameter



SL1-150		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 150mm	Labeling Speed 150 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3/8" Diameter Max: 5" Diameter



SL2-400		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 16mm Max: 400mm	Labeling Speed 200 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 6 1/4" Diameter Max: 10" Diameter



SL1-350		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 150mm Max: 300mm	Labeling Speed 50 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 3 3/4" Diameter Max: 5" Diameter



SL2-500		
Dimensions Height: 73" (1854.2 mm) Length: 36" (914.4 mm) Depth: 78" (1981.2 mm)	Label Size (Lay Flat Size) Min: 350mm Max: 400mm	Labeling Speed 200 CPM*
Weight Approx: 350 lbs. (158.75 kg)	Electrical Requirements 110VAC - 15 AMPS (220VAC Optional)	Container Sizes Min: 8 3/4" Diameter Max: 11 1/2" Diameter

*Speeds, film sizes, and available options vary depending on machine model and project specifications. Contact your sales representative for individual machine details.